



**VT- 09CBJ43-A**

**Stainless Steel Explosion Proof Power Box**

## Features

- Aluminum
- 4\*G3/4" interface
- Slight anti-corrosion
- C-level Explosion-proof
- Explosion-proof, anti-corrosion, waterproof
- four-way junction box for cable connection



# V.TECH

## Specification

### VT-09CBJ43-A

### Stainless Steel Explosion Proof Power Box



Aluminum  
Power box  
B-level Explosion proof  
Explosion-proof, anti-corrosion, waterproof  
4\*G3/4" interface  
Slight anti-corrosion

Product	Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db
	Ingress Protection level	IP68
Other specifications	Temperature range	-40°C ~ 60°C
	Relative humidity	≤ 95% (+25°C)
	Atmospheric pressure	80kpa ~ 106 kpa
	Thermostat System	Optional
	Supply voltage	DC12V/24V /AC220V
	Suitable envirment	Apply to explosive gas and combustibile dust environment
	Material	Aluminum
	External dimensions	200mm*200mm*90mm
	internal and external size can OEM	
	Inlet hole specifications	G3/4" X 4
Installation method	PTZ, Wall Hanging dyadic, fixed bracket, Pillar base	