



VT-BC504W

250-degree High Temperature Housing

Features

- ATEX Zone 1&2 / 21&22
- 250-degree high temperature Housing
- double-layer structure, water & wind cold
- inside size: $\Phi 100 \times 300$ mm window size: $\Phi 75$ mm
- Made of 304 stainless steel material (316,316L for optional)



V.TECH

Specification

VT-BC504W

250-degree High Temperature Housing



250-degree high temperature Housing
 double-layer structure, water & wind cold
 use high temperature window which can up to 250 degree
 Made of 304 stainless steel material. apply to strong corrosive environment

Ingress Protection level	IP66
Working temperature	-10°C~250°C
cooling water temperature	≤30°C
Cooling water flow	0.3~0.4m ³ /h
the working cooling water pressure	0.1~0.2Mpa
pressured air temperature	≤30°C
Air pressure	0.1~0.3Mpa
air flow rate	0.1~0.2m ³ /min
Relative humidity	≤95% (+25°C)
Atmospheric pressure	80kpa~106 kpa
Supply voltage	DC12V /AC220V optional
Material	304 stainless steel
inlet interface specifications	G1/4 for air and water cooling, G1/2" x 2 for output cable
External dimensions	351.5x140x182.5mm
inside dimension	Φ100mm*300mm (length)
Windows area	Φ60
Installation Method	PTZ, Wall Hanging dyadic, fixed bracket,
	Pillar base