

## Features

- ATEX Zone 1&2 / 21&22
- smart windshield wiper optional
- Made of 304 stainless steel material (316,316L for optional)
- Low power consumption, the fuselage internal air convection heat dissipation design, can work continuously for a long time
- Well design for Explosion-proof, anti-corrosion, waterproof, suitable for indoor and outdoor environment
- Class I Division 1&2 / Class II Division 1&2 and all the rest except zone 0



### VT-PW601

### ATEX Certificated Stainless Steel Explosion Proof Housing



Smart windshield wiper

The module circuit design, support baud rate/ control protocol automatic recognition, support software address code setting.

Imported precision motor, Response sensitivity, stable operation, low accuracy, no jitter under any speed

Windows glass surface process by nanotechnology. Well light transmittance. no halation effect. non-stick oil/dusty

Low power consumption, the fuselage internal air convection heat dissipation design, can work continuously for a long time

Made of 304 stainless steel material. apply to a strong corrosive environment

Well design for Explosion-proof, anti-corrosion, waterproof, suitable for indoor and outdoor environment

Product	Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db
	Ingress Protection level	IP66
PTZ function	Rotation range	Horizontal : 0~360° Vertical: : ±90°
	Rotation speed	Horizontal : 0.1°/S~40°/s Vertical: : 0.1°/S~40°/s
	monitoring location	255 locations can be set
	Communication method	RS485
	Boad rate	2400 / 4800 / 9600 bps
	Communication protocol	PELCO—D、 PELCO—P etc.
	monitoring location setting accuracy	±0.1°

Interface	Audio input	1 path
	Audio output	1 path
	Alarm input	1 path ( optional )
	Alarm output	1 path ( optional )
	interface protocols	ONVIF、PSIA、CGI
Other specification	Temperature range	-40°C~60°C
	Relative humidity	≤ 95% (+25°C)
	Atmospheric pressure	80kpa~106 kpa
	Material	304 stainless steel (316, 316L for optional)
	Supply voltage	AC85V-260V
	Inner Size	Φ106*220mm
	Window	Φ65mm
	Inlet hole specifications	G-3/4"x 1
	Electrical connection	10-core composite cable
	Thermostat System	Optional
	Installation method	bracket or base installation
	weightNN	18.5Kg