

## VT-SP120-25W

V-TECH Explosion Proof POE Speaker

IP67

120  
dB



- ATEX Zone 1 & 2 - 21 & 22
- **Certification:** ATEX , CNEX
- Strong system expansion compatibility, support standard SIP 2.0 (RFC3261) and related RFC protocols
- It can realize broadcast, single call, group call and other functions when used together with IP server
- **NOTE:** Need to be registered on the IP server to use

## EX Marking



## Certification



## Markets



|                                                                                   |                                |                                           |
|-----------------------------------------------------------------------------------|--------------------------------|-------------------------------------------|
|  | Ex-Level                       | Ex dib IIC T6 Gb<br>Ex tD A21 IP66 T80 °C |
|                                                                                   | Ingress Protection level       | IP66-67                                   |
| specifications                                                                    | Model                          | VT-SP120-25W                              |
|                                                                                   | Rated Voltage                  | POE                                       |
|                                                                                   | Network Communication Protocol | TCP, UDP, ICMP, IGMP                      |
|                                                                                   | Power                          | 25w                                       |
|                                                                                   | Impedance                      | 8Ω                                        |
|                                                                                   | Frequency Response             | 250~3000 Hz                               |
|                                                                                   | Material                       | Aluminum Alloy                            |
|                                                                                   | Ringer Volume                  | 120dB                                     |
|                                                                                   | Corrosion Grade                | WF2                                       |
|                                                                                   | Ambient Temperature            | -30~+60°C                                 |
|                                                                                   | Atmospheric Pressure           | 80~110KPa                                 |
|                                                                                   | Relative Humidity              | ≤95%                                      |
|                                                                                   | Lead Hole                      | 1-G3/4"                                   |
|                                                                                   | Dimensions                     | 300×415 (mm)                              |
|                                                                                   | Weight                         | 7.5 KG                                    |
|                                                                                   | Installation                   | Wall-mounted                              |